



AMPLIFIERS/ COMPACT AMPLIFIERS/ eCA120

Applications

- Classrooms
- Meeting rooms
- Multimedia presentations (in combination with video projectors, screens, etc.)
- Retail shops
- Museums and exhibitions
- Videowalls, screens, interactive
- AV marketing and digital signage

Stereo Micro-Amplifier

ECLER eCA120 is a 2 x 60 W RMS @ 4 ohms stereo micro-amplifier, in a very compact format and a light and silent (fanless) design. It features 1 LINE stereo input, AUTO STANDBY function and volume remote control, compatible with ECLER WPmVOL and WPmVOL-SR wall panels (0-10 VDC). External, universal and CE/UL/CCC certified power supply.



Key Features

- 2 x 60 W RMS @ 4 Ω stereo amplifier
- External, universal power supply
- AUTO STANDBY function: in the absence of an audio signal the unit automatically goes into STANDBY mode, minimizing power consumption
- Light and silent (fanless) design
- 1 unbalanced stereo line input (LINE IN / STACK), with dual RCA connector and 3-pin Euroblock connector
- Local volume control by knob
- Remote volume control by WPm series wall panel (0-10VDC)

Main Technical Specifications	Power	2 x 60 W RMS @ 4 Ω			
	Inputs	1 x stereo, LINE level (double RCA and Euroblock terminals)			
	Outputs	1 x stereo powered output (Euroblock terminals)			
	Dimensions / weight	H: 48 mm	L: 90 mm	W: 190 mm	600 g
	Others	Universal & certified external power supply REMOTE volume control port (0 - 10 VDC) Auto stand by feature			

Accessories

- WPm series wall panel controls



WPmMIX-T